

Very Narrow Aisle Forklift

Used Very Narrow Aisle Forklift Michigan - Warehousing solutions often focus on layout and space saving solutions in order to cut down on costly square footage and decrease travel time required to transport goods throughout the warehouse and loading dock areas. Narrow aisles need specific solutions to allow goods to be accessed and stored properly. More space can be given to storage as less space is needed for accessing the aisle. Warehouse optimization consists of warehouse configurations. Warehouse Optimization Several benefits can be enjoyed for adding very narrow aisle warehouse optimization such as more storage space for the facility. Since very narrow forklift trucks have been designed to take up significantly less space, warehouse aisle widths can be reduced to half the width needed by traditional forklifts. Numerous narrow aisle forklifts deliver better stacking heights to increase the storage capacity on a square foot basis. This means that costs are decreased because less warehouse space is necessary for the same amount of stock than if a standard aisle configuration were used. Square footage is costly in urban areas and any way to reduce warehousing costs can save a company money. When planned carefully and properly, it is possible to increase warehouse storage area by up to 80 percent by implementing a very narrow aisle width configuration. This warehouse design creates more rack faces and increased product access. Since greater quantities of products are situated in a more accessible area, there is less travel time needed for gathering and storing items. Warehouse layouts usually utilize a narrow aisle or very narrow aisle plan. Narrow aisles are usually those that use less than 11 feet of aisle width. Very narrow aisles usually use an aisle width of approximately 6.5 feet across. Storage options are greatly increased with these aisle width options. However, they also create challenges when turning within the aisles using forklifts for stocking and order picking. These challenges are met by using very narrow forklifts to gain access and complete tasks. Before choosing a forklift for a particular job, it is vital to know the dimensions of the aisle. It is important to have the correct aisle dimensions before forklift shopping to avoid securing a machine that won't fit its' intended location. Finally, it is critical that any utilities, posts or columns are taken into account before settling on a specific narrow aisle forklift design as these may affect access to aisles by some forklifts or prevent warehouse optimization.

Very Narrow Aisle Forklift Trucks Very narrow aisle forklift trucks are almost always powered electrically, usually by rechargeable battery. Stand-up riders are a popular design for very narrow aisle forklift trucks. The most commonly used types of very narrow aisle forklift trucks are: 1. Reach trucks 2. Order pickers; 3. End-control riders; and 4. Turret or swing-mast. **Reach Forklift Trucks** Reach trucks were designed as a version of the rider stacker forklift but specially modified for use in narrow aisles. It got its name by its function of reaching its forks forward to get to a load. The moving mast and the moving carriage are two types of reach trucks. The moving carriage works by raising and lowering the carriage, along with the operator. While the operator stays at ground level, the moving mast is responsible for raising and lowering the forks. The moving mast reach truck is generally considered the safer of the two types of reach trucks. Reach trucks utilize a pantograph system that is a jointed framework design enabling the driver to place and reach loads without moving the forklift. **Order Pickers** Order pickers were created to specifically pick orders from difficult-to-access racks. These machines are used for picking up lighter stock that can be moved by hand. These order pickers work by lifting the operator up to the level of goods in order to identify and pick the specific item or items necessary to fill an order. **End-Control Riders** End-control riders are machines that pick loads up at floor level and move the items horizontally as opposed to lowering or lifting over numerous heights. **Turret or Swing-Mast Forklift** Turret or swing-mast very narrow aisle forklift have a pivoting articulating swivel mast. The mast swivels to enable pallets to be positioned on the right or left side of the forklift. **Guided Very Narrow Aisle Trucks** Very narrow aisle forklift trucks can be guided by rail or wire down the aisles. Since the forklift truck is guided, the chance of colliding with racks while traversing down the aisles is very low. Rail-guided applications use special rails set into the floor on either side of the aisle,

funning the length of the location and curving around the edge. The forklift is fitted with special wheel guides that slide into the rails, preventing the forklift from moving outside the rail guards. The wire-guidance system requires that the wires be installed into the floor, along the center of the aisle. The wire-guides function similarly to the rail systems except the forklift has a wire-guide system to prevent the machine from traveling where it is not supposed to.

Work Site Considerations To use a narrow aisle configuration, there are some key considerations that need to be made. The floor and the rack construction needs to be evaluated to avoid any issues since the very narrow aisle units have extremely high racking systems. Four specific areas need to be perfectly prepared before a racking system can be implemented including a level floor, plumb racks, any floor cracks need to be repaired and the floor's load capacity must be accurate. These locations need to be maintained and monitored continuously.

Level Floor Due to the racking system height, any minor floor slope can gravely impact how plumb the racks are, particularly over time if loads are placed and removed repeatedly on the racks. The height of the racking system means that any minute floor slope can have a negative impact on how straight the racks are, especially over time when loads are continually removed and placed on the racks. Without this foundation of a level floor, the stability of the racks could be jeopardized.

Crack Repair When there are floor cracks found, they need to be assessed and immediately fixed for safety concerns. Safety can become compromised when flooring cracks become 3/8 inches wide. They require proper filling with a substance that is as hard as the floor.

Floor Load Capacity The floor needs to meet specific minimum requirements prior to a narrow aisle configuration. Minimum flooring requirements include concrete measuring three thousand psi and rebar distributed evenly three to four inches below the surface. Depending on the load requirements and configuration, additional reinforcements may be needed.

Plumb Racks Installing the racks safely and correctly is vital for the entire system. Rack failure can happen if they are improperly installed. Every rack needs to be plumb to ensure a safe system and work environment. Rack shims can help the rack stay plumb to one inch at the height of thirty feet. If the above measures are not taken or are improperly implemented, it is likely to cause a racking failure. Racking failure can kill or injure employees, damage equipment and result in horrible damage. Due to these potential problems, the most significant part of creating a narrow aisle configuration for warehousing optimization is the initial measurements.